


TYPE

[W:Automatic alternate parallel operation]

■ External relay output ※2

【Contact rating】

AC250V 1A
(inductive load)



No. CC 4 - 26575 - 0 1/2

給水ユニット接続図

TYPE

機種：NX-VFC

[D:Automatic alternate operation]

[W:Automatic alternate parallel operation]

- ※1 This is connected when the interlock function is used. Though the interlock input signal is the make contact when delivered, it can be changed to the break contact by settings.
- ※2 Content of the external relay output can be change by settings.
For further details, see the connection pattern diagram.
- ※3 Depending on the setting, the system can be expanded to double receiver tanks, 5P electrodes and solenoid valves. For further details on the wiring, see the connection pattern diagram.
Voltage of solenoid valve is 200V. Total current of solenoid valve must not exceed 0.3A.
- ※4 This terminal is for the cooling fan of outdoor guard. Please do not use other equipment.
- ※5 The low temperature sensor and heater for the freeze prevention system are provided as part of special specifications.
- ※6 Please do not use this connector.

仕様 SPEC.	出力 OUTPUT	0.4~7.5	kW
	相・電圧 PHASE & VOLTAGE	3 φ	380/400/400-440 V
	周波数 FREQUENCY	50/60	Hz

機器名称 ITEM NAME		機器番号 ITEM No.	
型式 MODEL		数量 QUANTITY	